

**NEW!** | CINEMA SERIES

# Punch Daylight Cinema

The AAdynTech Punch Daylight Cinema is the most powerful daylight-balanced white light professional LED fixture available today. Now the Punch is coupled with high CRI (92+) performance to create the Punch Daylight Cinema fixture. Flicker free up to 12,000 fps, the fixture delivers an incredible output of 3,716fc @ 10 feet, while consuming less than 5 amps of power. The Punch Daylight Cinema is self-contained with a universal power supply and, unlike traditional HMI's, the need for heavy and expensive head cables, ballasts or spare lamps is eliminated, dramatically reducing transport weight. Crew and talent safety is always a concern and the Punch Daylight Cinema generates minimal heat and can be held with bare hands, and harmful UV or IR emissions are virtually eliminated. Instant 'ON' ensures no warm-up wait time on set. The Punch Daylight Cinema comes with a built-in Wireless Capable DMX/RDM Receiver. This model may be operated in either wired or wireless configuration further expanding its versatility.

Specially designed four holographic lenses provide optical efficiency by creating a single light source, effectively eliminating multiple shadows. These four quick change lenses are included to adjust the beam angle for a very narrow, narrow, medium or flood while maintaining a flat, even field. The UIM Digital Remote provides precise control over dimming with user selectable variable dimming curves, a smart lamp hour counter, multiple memory recordings and a host of other features including strobe and lightning effects. A heavy-duty yoke is provided.



THE PUNCH PLUS IS AVAILABLE IN DAYLIGHT. SPECIAL ORDER MODELS INCLUDE: BULLET & MEGA BULLET HIGH SPEED VERSIONS.

©2023 Sturdy Corporation. All rights reserved. As technical advancements continue, all specifications are subject to change without notice.



**FEATURES AT A GLANCE:**




- 92+ CRI across entire brightness range
- 3,716 foot candle output @ 10 feet
- 5600K CCT
- Draws only 4.8 amps at full output
- Auto range voltage - 100/277 VAC - 50/60Hz
- Up to 90% energy savings
- Same size and uses the same accessories as Punch Daylight
- Precise brightness control w/ variable dimming curve
- Single light source eliminates multiple shadows
- Flicker-free up to 12,000 fps
- No heat generation - operates cool to the touch
- Douse button (momentary off)
- Included 5°, 15°, 30°, 55° lenses to vary beam angle
- No head cables, ballast or spare lamps
- Built-in digital User Interface Module (UIM) control
- Recalibration countdown hour 'smart' meter
- Wireless Capable or wired DMX In/Out or digital remote
- PowerCon AC Cable
- Programmable multiple lightning and strobe effects
- Multiple user memory storage with recall
- 2 year warranty on fixture
- Operating temperature at -20c to +50c
- Certified UL, ETL, CSA, CE & RoHS compliant

# Punch Daylight Cinema

NO DIFFUSER	@10 FEET	@15 FEET	@20 FEET
Lux	40,000	17,613	9,837
Foot Candles	3,716	1,636	914
5° DIFFUSER	@10 FEET	@15 FEET	@20 FEET
Lux	39,200	14,310	8,240
Foot Candles	3,642	1,330	765
15° DIFFUSER	@10 FEET	@15 FEET	@20 FEET
Lux	25,450	11,628	6,520
Foot Candles	2,364	1,080	606
30° DIFFUSER	@10 FEET	@15 FEET	@20 FEET
Lux	13,960	6,230	3,665
Foot Candles	1,297	579	340
55° DIFFUSER	@10 FEET	@15 FEET	@20 FEET
Lux	5,462	2,852	1,570
Foot Candles	507	264	146

DIFFUSER	BEAM ANGLE	FIELD ANGLE
0°	13.3°	18.9°
5°	16.2°	26.3°
15°	18.3°	33.4°
30°	28.1°	50.1°
55°	45.3°	76.7°

At 90° angle to incident surface



## SPECIFICATIONS

Control	UIM, Wired & Wireless Capable DMX/RDM
Source	LED, 5600K CCT, 92+ CRI
Cooling	Passive/Active
Mounting	Junior Pin/28mm Spigot
Certifications	ETL, UL, CSA, CE and RoHS Compliant

## DIMENSIONS


Length	431.4 mm	17.0 in.
Width	468.9 mm	18.5 in.
Height	515.5 mm	20.3 in.
Weight	22 kg	48.4 lbs

## POWER

Input Voltage	100-277 Vac
Input Freq	50/60 Hz
Input Current	4.87 Amp @ 120V 584.4 W @ full
Connection	PowerCon Twist Lock connector

## HIGHLIGHTS

- RoHS Compliant
- Up to 3,716 foot candles @ 10 feet
- Daylight-Balanced at 5600K CCT
- Dimmable with no color shift
- Draws 4.8 amps at max output
- No harmful UV or IR radiation



©2023 Sturdy Corporation. All rights reserved. As technical advancements continue, all specifications are subject to change without notice.